

60246-142
9639AMENDMENTIN THE CLAIMS:

-
1. (AMENDED) A method for making a heat exchanger of a furnace system comprising the steps of:
applying a layer of an oxidizable material on an inner surface and an opposing outer surface of said heat exchanger; and
oxidizing said layers of oxidizable material to form a layer of dark material having a high emissivity on each of said inner surface and said outer surface.
 2. (AMENDED) The method as recited in claim 1 wherein the step of applying said layers of said oxidizable material includes applying said layers of oxidizable material electrochemically.
 - A¹ 3. (AMENDED) The method as recited in claim 1 wherein step of oxidizing said layers of oxidizable material includes utilizing an oxidizing alkaline solution to oxidize said layers of oxidizable material.
 4. (AMENDED) The method as recited in claim 1 wherein said layers of oxidizable material are copper.
 5. (AMENDED) The method as recited in claim 4 wherein said layers of oxidizable material are oxidized to cupric oxide.
-

Please delete claim 8.

21. (NEW) The method as recited in claim 3 further including the step of spraying said oxidizing alkaline solution on said layers of oxidizing material.
- A²

60246-142
9639

conceded
A2

22. (NEW) The method as recited in claim 3 further including the step of immersing said heat exchanger with said layers of oxidizable material in said oxidizing alkaline solution.
-